


Comlinear™ CLC2500

Dual, Ultra-fast Voltage Comparator



General Description

The *Comlinear* CLC2500 is a sub-nanosecond dual comparator with propagation delay variation less than 100ps from 5 to 50mV input overdrive voltage. The input slew rate is 10 V/ns and the differential input stage has a common-mode input range of -2.5V to 4V.

The *Comlinear* CLC2500 has ECL-compatible complementary digital outputs that are capable of driving 50Ω terminated transmission lines. The CLC2500 is ideally suited for automated test equipment (ATE) applications, high-speed instrumentation, and peak detection.


FEATURES

- 650ps propagation delay
- 100ps overdrive delay variation
- 70dB CMRR
- Differential latch control
- 10V/ns slew rate
- ECL compatible
- 350mW power dissipation
- 900MHz bandwidth
- Lead-free PLCC-20 package

APPLICATIONS

- Automated test equipment
- High-speed instrumentation
- Window comparators
- High-speed timing
- Line receivers
- High-speed triggers
- Threshold detection
- Peak detection

Block Diagram



Ordering Information

Part Number	Package	Pb-Free	Operating Temperature Range	Packaging Method
CLC2500IPL20X*	PLCC-20	Yes	-40°C to +85°C	Reel
CLC2500IPL20*	PLCC-20	Yes	-40°C to +85°C	Tray

Moisture sensitivity level for all parts is MSL-1.

*Preliminary

Electrical Characteristics

T_A = 25°C, V_{CC} = 5V, V_{EE} = -5.2V, R_L = 50Ω to -2V; unless otherwise noted.


Parameter	Conditions	Min	Typ	Max	Units
AC Performance					
Propagation Delay	20mV overdrive		650		ps
Latch Set-up Time	20mV overdrive		150		ps
Latch to Output Delay	20mV overdrive		500		ps
Latch Pulse Width	20mV overdrive		500		ps
Latch Hold Time	20mV overdrive		0		ps
Rise Time	20% to 80%		180		ps
Fall Time	20% to 80%		80		ps
Slew Rate			10		V/ns
-3dB Bandwidth			900		MHz
DC Performance					
Input Offset Voltage ⁽¹⁾		-10	3	10	mV
Average Drift			10		μV/°C
Input Offset Current ⁽¹⁾		-3	1	3	μA
Input Bias Current ⁽¹⁾		-25	8	25	μA
Positive Supply Current			18	30	mA
Negative Supply Current			40	55	mA
Positive Supply Voltage		4.75	5.0	5.25	V
Negative Supply Voltage		-4.95	-5.2	-5.45	V
Input Common Mode Range		-2.5		4.0	V
Latch Enable	Common Mode Range	-2.0		0	V
Open Loop Gain			66		dB
Differential Input Resistance			500		kΩ
Input Capacitance			0.6		pF
Power Supply Rejection Ratio			70		dB
Common Mode Rejection Ratio	V _{CM} = -2.5V to 4V		70		dB
Power Dissipation	Both Channels, No Load		350	425	mW
	Both Channels, with Load		400	550	mW
Output High Level	ECL 50Ω to -2V	-1.00		-0.81	V
Output Low Level	ECL 50Ω to -2V	-1.95		-1.54	V

Notes:

1. 100% tested at 25°C. Refer to the data sheet for complete product specifications.

Available Package

CLC2500 PLCC-20
(not actual size)



For additional information regarding our products, please visit the CADEKA at: cadeka.com

CADEKA Headquarters Loveland, Colorado

T: 970.663.5452

T: 877.663.5415 (toll free)

CADEKA, the CADEKA logo design, and Comlinear and the Comlinear logo design, are trademarks or registered trademarks of CADEKA Microcircuit LLC. All other brand and product names may be trademarks of their respective companies.

Copyright ©2007 by CADEKA Microcircuit LLC. All rights reserved. 0707

